

MOT

Thermal Transfer Overprinter



Proven Reliability

Engineered with top-tier components and rigorously tested across multiple industries to ensure reliable, fail-safe performance.

Exceptional Range of Material Compatibility

Compatible with a broad selection of ribbons designed for diverse substrates, including those requiring high-temperature resistance and anti-migration properties.

Superior 300DPI Print Quality

Ensures precise, high-resolution codes and visuals through cutting-edge synchronous printing.

Modular Design


Features a user-friendly 7-inch touchscreen and easy ribbon loading for seamless integration.





Parameters

Type	MOT32	MOT53
Resolution	300DPI	300DPI
Inter. Print Area	32 x 55mm	53 x 55mm
Cont. Print Area	32 x 120mm	53 x 120mm
Ribbon length	600M	600M
Standard Ribbon width	33mm	55mm
Print Mode	Intermittent and Continuous Integration	
Left and right	Optional	
Cont. Print Speed	50~600mm/s	
Max prints	220packs/min	
Print contents	Date, post date, time, counter, shift, Bar code, QR code, LOGO, text	
Input	Print signal, Encoder signal (NPN, PNP)	
Output	Fault relay output	
Dimensions (mm)	164X158X166	164X158X187
Printer weight	6.8Kg	7.0Kg
Power Supply	110/220V AC, 50/60 Hz, 120W	
Operation Environmental	Temperature: 5~40°C Humidity: 10%~90%, non-condensing	
Operating interface	7-inch touch screen, multi-languages available	
Air supply	No need air supply	


Dimension



▲ MOT32



▲ MOT53



Controller size

